



TACKLERS

Rising by lifting since 1973

Authorised dealer for: Crosby, Ferrotiger, Indef, Titan, UMI, Youngman & Zebra

Shop no 1 to 4 Laxminarayan Society, Building B, 285 Koregaon Road, Opp. Bund Garden Water Pumping Station, Pune 411001, Maharashtra, India

Email: info@tacklers.co.in, farah@tacklers.co.in

Telephone: (020)26122595

FRP INDUSTRIAL STEP LADDER



Fig 1: Industrial Step Ladder 10 (Aluminium Steps With Steel Brace)

APPLICATIONS

- In Safe Electrical Maintenance.
- In Chemical Industry.
- In Food Industry.
- In Industrial and Commercial establishments.
- In Malls, Shops, Theatres, Housing Societies, Corporate Offices, Factories, etc.

ADVANTAGES

- Electrically resistant.
- Flame retardent.
- Higher tensile strength as compared to Aluminium therefore, stronger.
- Corrosion & rust resistant and hence all-weather proof & suited to outdoor use.
- Dust & water proof.

SPECIFICATIONS

- Rated for 110 Kg.
- The FRP Section size is 80 x 28.5 x 3.0mm notable for their yellow colour and non-conductive (up to 30,000 volts) properties.
- The treads are Aluminium alloy, self corrugated, 80 x 39 x 1.5mm and anti-slip.
- The ladders have comfortable steps, with sufficient foot rest and a molded top seat to place small tools.
- The ladder has anti-skid rubber shoes, steel spreaders & steel braces on steps.
- The back frame is reinforced for additional heavy duty construction.

Model No.	Size	Spacing between Steps (in mm.)	Approx. Packed Size (in mm)	Approx. Height of Top (in mm)	Approx. Footprint when open (in mm)	No. of Steps	Approx. Weight (in Kg.)
FRP 8 (Industrial)	8 Ft.	300	2673 x 688 x 223	2436	1595	8	17
FRP 10 (Industrial)	10 Ft.	300	3271 x 772 x 223	2991	1937	10	20
FRP 12 (Industrial)	12 Ft.	300	3870 x 855 x 223	3545	2279	12	25
FRP 14 (Industrial)	14 Ft.	300	4468 x 939 x 223	4101	2621	14	28